

Applications of Computational Fluid Dynamics Simulations in Urban Environments and Experiments Designed to Aid the Development and Evaluation of these Models

Shinn, J. H., Gouveia, F. J.

This article was submitted to 2001 International Symposium on Environmental Hydraulics, Tempe, Arizona, December 5-7, 2001

U.S. Department of Energy

Lawrence
Livermore
National
Laboratory

August 2001

DISCLAIMER

This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor the University of California nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or the University of California. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or the University of California, and shall not be used for advertising or product endorsement purposes.

This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

Applications of Computational Fluid Dynamics Simulations in Urban Environments and Experiments Designed to Aid the Development and Evaluation of these Models

Joseph H. Shinn and Frank J. Gouveia

Energy and Environment Directorate, Lawrence Livermore National Laboratory, P.O. Box 808 L-396, Livermore, CA 94551-0808.

Abstract

Progress in development of CFD models has shown their great potential for prediction of air flow, heat dissipation, and dispersion of air pollutants in the urban environment. Work at Lawrence Livermore National Laboratory has progressed using the finite element code FEM3 which has been “massively parallelized” to produce flow fields and pollutant dispersion in a grid encompassing many city blocks and with high resolution. (See the related papers in this Proceedings). While it may be argued that urban CFD models are not yet economical for emergency response applications, there are many applications in assessments and air quality management where CFD models are unrivaled in the level of detail that they provide. We have conducted field experiments to define the flow field and air tracer dispersion around buildings as a means of critiquing and evaluating the CFD models. The first experiment, the “B170 study”, was a study of flow field, turbulence, and tracer dispersion in separation zones around a complex, single building. The second was the URBAN 2000 experiment in downtown Salt Lake City where flow fields and tracers were studied in nested resolution from the single building scale up to larger scales of 25 city blocks, and out to 6 km. For the future an URBAN 2003 experiment is being planned. We review the salient features of these experiments.

A “breakthrough” technology in urban diffusion modeling is the use of *modified* computational fluid dynamics models (CFD) that use the meteorological conventions of large eddy simulation to represent the flow field (1). These CFD models have been initialized from the output of mesoscale atmospheric models with 4 km grid resolution, apparently with no problems although questions remain about aliasing and sources of bias. While more work remains, it is clear that should progress continue a remarkable tool should be available for such applications as:

- Vulnerability studies for chemical, biological, and nuclear terrorism
- Assessments of air quality for urban pollutants—CO, NO, O₃, and particulates
- Preparing for disease outbreaks which are transmitted by wind
- Inhalation exposure attribution downwind of industrial releases
- Mitigation of susceptible populations of exposed individuals

- Mitigation of problems *inside buildings* through heating and ventilating intakes
- Planning for emergency response where scenarios may be studied beforehand

Simulations and experiments in these complex cases have been made to interact. We have used rough case studies with CFD models to plan the experiment (2,3). That is, since measurement resources are limited they should be placed where we should get the most gain in developing or evaluating the models. Eventually the knowledge about the urban atmosphere is summarized and tested in the models. Of course, we have utilized wind tunnel or water channel data to evaluate the models as well. But the large scales of motion in the atmosphere and the complex urban heat island and turbulent wake mixing in real urban settings have made it necessary to have prototype experimental data.

Urban meteorology or *urban fluid mechanics* is an evolving field (4) with many challenges to define the surface boundary layer and thermal influences. But the need is great with so many people living in the urban zones, and there will be an eventual demand for the weather forecasts to be made for specific land use zones (5).

B170 Experiment. We conducted a series of experiments in 1999 and 2000 at a complex building, B170 (the National Atmospheric Release Advisory Capability housing the Atmospheric Sciences Division and the Energy and Environment Directorate) at Lawrence Livermore National Laboratory (6). B170 is a 3-story building with a courtyard, a tangentially-sited auditorium, and alcoves along its side. We used arrays of sonic anemometers to map the horizontal flow-field below the mid-height of the building for a range of inflow wind directions. Approximately 50 anemometer locations were recorded. We also have one-second turbulence files for 6 locations along the building sides. Generally speaking, we have the more detailed flow-field data for wakes and separation zones than for well-behaved flows along parallel walls. In 2000 we utilized the air tracer SF₆ to determine concentration fields in separation zones along the ground. While these data are not extensive we were able to compare the results to output from CFD models with good results (7). In the case of flow vectors, the FEM3MP model was within 15% of vector magnitude when averaged over the whole domain. The model had less success with the separation wake in the lee of the building than with the side separation zones, however. The data from this study are publicly available for anyone with similar interests in model development and evaluation.

URBAN 2000 Experiment. In October 2000, a collaborative experiment was conducted involving more than 100 scientists, planned and led by a consortium (8) of three National Labs: Pacific Northwest National Lab (K. J. Allwine), Lawrence Livermore National Lab (J. H. Shinn), and Los Alamos National Lab (G. Streit). The members of the Vertical Transport and Mixing Project (VTMX) provided the backbone of regional sounding data, while URBAN 2000 provided building scale data out to 6 km. This was a night-time experiment with 18 one-hour releases of air tracers carried out by NOAA Air Resources Laboratory Field Research Division (K. Clawson). Other participants were the UK Defence and Evaluation Research Agency (I. Griffiths) and a meteorology contingent from Dugway Proving Ground (C. Biltoft). At the “building scale” 45 tracer bag samplers, multiplexed gas analyzers, 12 2-D sonic anemometers, 2 3-D sonic anemometers, and 1 lidar density vertical profiler (Vaisala Corporation) were set up within one city block. At the “urban” scale (25-city blocks) were 64 tracer bag gas samplers, 1

mobile tracer analyzer, 9 wind stations, 3 2-D sonic anemometers, 6 3-D sonic anemometers, and 1 acoustic sodar. At the 1 to 6 km scale there were 36 tracer bag samplers, 4 mobile tracer analyzers, 6 wind stations, acoustic sodars, 1 radar wind profiler, 60 temperature loggers, and the *WindTracer* doppler lidar mapping the radial wind components from an observation location above the city. At the “regional” scale there was a mix of VTMX and URBAN 2000 participants who operated 50 tracer bag samplers, 1 mobile tracer analyzer, 32 mesoscale wind stations, 6 radar wind profilers, 7 acoustic sodars, 3 rawinsonde balloon sites, 4 tethered sites, 10 sonic anemometers, and a doppler lidar (R. Banta, National Center for Atmospheric Research) to determine cold-air inflow from canyons. Summaries of the VTMX Experiments (C. Doran) and URBAN 2000 Experiment (K. J. Allwine) are in process in the *Bulletin of the American Meteorological Society*.

These 18 tests constituting the Experiment were conducted 3 per night every other hour beginning 7 October and ending on 26 October. There were ten Intensive Observation Periods (IOP), six of which used SF₆ air tracer. The initial data analysis was agreed to be on IOP 10, and some of these results are being presented at the Conference. At this time, the URBAN 2 Experiments can be reviewed on the World-Wide Web through Lawrence Livermore National Laboratory Website, but the data are available only to those who participated and have been issued a password. Eventually, the collaborators will make this data available to the public after they have an opportunity to publish their own papers.

Planning the URBAN 2003 Experiment. A second large-scale experiment similar to the above is planned for 2003. The choice of cities has been narrowed to either Oklahoma City or Phoenix. The purpose of URBAN 2003 is to provide evaluation data for models where the boundary layer is a daytime, convective case. Much work remains to be done before the experimental details can be released but it is clearly going to involve many collaborators just as did URBAN 2000.

Acknowledgment

This work was performed under the auspices of the U.S. Department of Energy, the University of California at the Lawrence Livermore National Laboratory under contract No. W-7405-Eng-48.

References

1. Lee, R.L., S.T. Chan, J.M. Leone, D. E. Stevens, 1999: Airflow and dispersion around multiple buildings. UCRL-JC-132241, in *Proceedings of Air Pollution 99*, 27-29 July, San Francisco, CA.
2. Stevens, D. E., R. J. Calhoun, S.T. Chan, R.L. Lee, J. M. Leone, J. H. Shinn, 2000: Building scale simulations in support of field experiments around Salt Lake City, in *Proceedings of the Third Symposium on the Urban Environment*, 14-18 August, Davis, CA.
3. Brown, M., M. Leach, J. Reisner, D. Stevens, S. Smith, S. Chin, S. Chan, and R. Lee, 2000: Numerical Modeling from Mesoscale to Urban Scale to Building Scale, in *Proceedings of the Third Symposium on the Urban Environment*, 14-18 August, Davis, CA.
4. Fernando, H.J.S, S. M. Lee, J. Anderson, M. Princevac, E. Pardyjak, and S. Grossman-Clarke, 2001, Urban Fluid Mechanics: Air Circulation and Contaminant Dispersion in Cities, *Environmental Fluid Mechanics* 1:107-164.

5. Dabberdt, W.F. and J. Hales, Forecast Issues in the Urban Zone: Report of the Tenth Prospectus Development Team of the U.S. Weather Research Program, 2000, *Proceedings of the Third Symposium on the Urban Environment*, 14-18 August, Davis, CA.
6. Shinn, J. H., and F. J. Gouveia, 2000, An Experiment to Evaluate Models of Air Flow around a Building, in *Proceedings of the Third Symposium on the Urban Environment*, 14-18 August, Davis, CA.
7. Calhoun, R., S. T. Chan, R. L. Lee, J. M Leone, J. Shinn, and D. Stevens, 1999: Flow Patterns Around a Complex Building, UCRL-JC-135879, in *Proceedings of 11th Conference on Applications of Air Pollution*, 9-14 January 2000, Long Beach, CA.
8. Shinn, J. H., K. J. Allwine, and G. E. Streit, 2000: The DOE URBAN Field Program for 2000-2004, in *Proceedings of the Third Symposium on the Urban Environment*, 14-18 August, Davis, CA.

University of California
Lawrence Livermore National Laboratory
Technical Information Department
Livermore, CA 94551

